

ZINTRA ACOUSTIC IN 12MM

Zintra Acoustic Panel



Texture:

Lustre:

Transparency:

DESCRIPTION / FEATURES

The Zintra Acoustic Panel is the perfect solution for your application where acoustic performance as well as aesthetics are required. Zintra's wide range of colours and ease of use make it the ideal material for commercial, hospitality and institutional projects. Zintra Acoustic Panel features include: * Cost effective sound solution - NRC = 0.45 for 12mm, 0.75 for 24mm * 2800mm long sheets ideal for join-free floor to ceiling applications * Broad range of neutral and bright colours * Suitable for a multitude of applications; walls, ceilings, screens * Easily fabricated and installed * Pinnable

Find out more about the Benefits of Zintra and its NRC rating on the DOWNLOAD tab.

COMPOSITION	Zintra Acoustic Panel - 100% Polyester
FINISHES AVAILABLE	Zintra Panel - Matt. Available in 20 colours. View Finishes
SHEET SIZE	2800mm x 1225mm
THICKNESS	12mm. Also available in 3mm (5 colours)
WEIGHT	2.4 kg/m ²
INDOOR/OUTDOOR	Indoor only
WET AREAS	No
PATTERN REPEAT	N/A
SUGGESTED INSTALLATION	<p>Check out the DOWNLOAD tab for a complete Handling and Installation guide.</p> <p>Be sure to support the panel during installation to avoid bowing or creasing.</p> <p>Adhere to substrate using contact adhesive, Liquid Nails or Z clips.</p> <p>Panel can also be mechanically fixed using details similar to glass fittings.</p>
LEAD TIME	<p>4-6 weeks for customization</p> <p>2-3 weeks for plain panels, no cuts</p>
CUSTOMIZABLE	Colour - contact Crown Surface Solutions for details
THERMOFORMABLE	No
FIRE	Zintra

FIRE RATING	In accordance with ASTM-E84, Zintra™ Acoustic 1/2" Panels achieve a Class A Flame Spread - passes CAN ULC S102-10.
SUPPLIED AS	Sheet ready to install
FABRICATION	Stanley knife if required
REFINISHABLE	No
CARE INSTRUCTIONS	Zintra
ENVIRONMENTAL INFORMATION	Easily recycled through standard recycling channels

CARE INSTRUCTIONS

Remove spills immediately using damp, clean cloth.

Dab Zintra with a clean, soft white cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.

Avoid using wax polishes, solvents or concentrated abrasives.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Dab gently.

Repeat using only a clean, water dampened cloth to remove bleach concentration then pat dry with a lint free cloth.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Crown Surface Solutions for assistance.